



| Caliper                            | NEUTRAL WEISS |                  |            | Grade: 523      |              |
|------------------------------------|---------------|------------------|------------|-----------------|--------------|
| <b>Stiffness L&amp;W Stiffness</b> |               | g/m <sup>2</sup> | ISO 536    | <b>80</b>       | <b>± 3.0</b> |
| <b>L&amp;W Roughness Bendtsen</b>  |               | mm/1000          | ISO 534    | <b>106</b>      | <b>± 4</b>   |
| <b>Opacity</b>                     | MD            | mN               | ISO 2493   | <b>122</b>      | <b>± 22</b>  |
| <b>Brightness with UV CIE</b>      | CD            | mN               | ISO 2493   | <b>55</b>       | <b>± 15</b>  |
| <b>Whiteness</b>                   |               | ml/min           | ISO 8791-2 | <b>200</b>      | <b>± 50</b>  |
|                                    |               | %                | ISO 2471   | <b>min 90.0</b> |              |
|                                    | D65           | %                | ISO 2470   | <b>103.5</b>    | <b>± 1.5</b> |
|                                    |               |                  | ISO 11475  | <b>146</b>      | <b>± 3.0</b> |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001, ISO 14001 and OHSAS 18001.

SIGNIFICANCE OF VALUES: 2 SIGMA